


PNP 半导体三极管 Silicon PNP transistor
描述 / Descriptions

TO-126 塑封封装 PNP 半导体三极管。Silicon PNP transistor in a TO-126 Plastic Package.

特征 / Features 用途 / Applications

与 BD139 互补。用于中功率电路及开关电路。


Complement to BD139. Medium power linear and switching applications

内部等效电路 / Equivalent Circuit
引脚排列 / Pinning


PIN1 : Emitter PIN 2 : Collector PIN 3 : Base

放大及印章代码 / hFE Classifications & Marking

*HFE(1)分档及打印

分 档	1	2				印记见下 具体内容以打印为准
H _{FE} (1)	100~250	160~320				
打印 (简例)	16	25				
其 它 说 明	封装外形: TO-126 管脚排列: E、C、B					

极限参数 / Absolute Maximum Ratings(Ta=25°C)

参数 Parameter	符号 Symbol	数值 Rating	单位 Unit
Collector to Base Voltage	V _{CBO}	-80	V
Collector to Emitter Voltage	V _{CEO}	-80	V
Emitter to Base Voltage	V _{EBO}	-5.0	V
Collector Current - Continuous	I _C	-1.5	A
Base Current - Continuous	I _B	-0.5	A
Collector Power Dissipation	P _C	1.25	W
Collector Power Dissipation	P _C (T _c =25°C)	12.5	W
Junction Temperature	T _j	150	°C
Storage Temperature Range	T _{stg}	-55~150	°C

电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Collector to Emitter Breakdown Voltage	V _{CEO}	I _C =-30mA I _B =0	-80			V
Collector Cut-Off Current	I _{CBO}	V _{CB} =-30V I _E =0			-0.1	μA
Emitter Cut-Off Current	I _{EBO}	V _{EB} =-5.0V I _C =0			-10	μA
DC Current Gain	h _{FE(1)}	V _{CE} =-2.0V I _C =-150mA	40		250	
	h _{FE(2)}	V _{CE} =-2.0V I _C =-500mA	25			
	h _{FE(3)}	V _{CE} =-2.0V I _C =-5.0mA	25			
Collector to Emitter Saturation Voltage	V _{CE(sat)}	I _C =-500mA I _B =-50mA			-0.5	V
Base to Emitter On Voltage	V _{BE(on)}	V _{CE} =-2.0V I _C =-500mA			-1.0	V

电参数曲线图 / Electrical Characteristic Curve

